HOUND® CANNABIS BREATHALYZER – COLLECT + SEND QUICK REFERENCE STEPS FOR BREATH SAMPLE COLLECTION

1. CREATE

- Plug system in and press rear power button to turn on. Ensure system is configured prior to first use.
- Log in with username and password.
- Explain procedure and instruct donor to empty mouth before collection.
- Scan Lab Account Number barcode or enter manually to create collection event.
- Verify donor's identity per employer policy and enter donor's information on touchscreen.
- Select donor's preference for receiving a link to donor copy of CCF from dropdown menu.

2. CONNECT

- Ask donor to select a breath collection package. Advise donor to remain seated during collection.
- Check package use-by date and inspect package for damage.
- Open package and remove contents donor cartridge with connector, air cartridge, mouthpiece, and tamper-evident seals.
- Confirm the cartridge barcode printed on the white donor cartridge label (aka donor sample barcode) matches the cartridge barcode printed on the yellow air cartridge label (aka air sample barcode).
- Select Scan Cartridge button on touchscreen.
- Scan or manually enter cartridge ID from donor cartridge. Confirm ID on screen matches label.
- Insert air cartridge into port on top of base station and ensure it is fully seated in the port.
- Ensure donor cartridge is firmly seated in connector fitting at the end identified with a silver dot and with notches inserted into fitting.
- Attach donor connector fitting to port on front of base station, starting at the base and tilting upward.

3. COLLECT

- Ask donor to remove mouthpiece from its package and ensure mouthpiece is free of obstruction.
- Instruct donor to insert mouthpiece into round opening in the top of the donor cartridge.
- Select Begin Collection button on touchscreen.
- Instruct donor to breathe into mouthpiece for 2-3 minutes. Short pauses are allowed.
- Complete collection and follow guidance on touchscreen for post-collection steps.
- Instruct the donor to remove and discard the mouthpiece and return the cartridge to the collector.
- Remove lower cellophane wrapping from donor cartridge and unclip connector fitting from cartridge.
- Remove upper cellophane wrapping from donor cartridge.
- Disconnect air cartridge from base station and remove cellophane wrapping from air cartridge.

4. COMPLETE

- Ask donor to initial identified regions of donor and air cartridge labels.
- Date identified regions of donor and air cartridge labels.
- Place donor cartridge upright on the base of the Assisted Compression Equipment (ACE).
- Using two hands, pull ACE handle down and compress cartridge cover until ACE reaches its hard stop.
- Remove donor cartridge from ACE, taking care not to tip the cartridge when removing.
- Place cartridge upright on a flat surface and press cover down by hand to ensure a full compression.
- Complete the same compression steps for the the air cartridge.
- Disconnect connector from base station; discard tubing. Pumps will conduct 20-second purge cycle.
- Secure cover onto donor cartridge with a tamper-evident seal, starting the seal at the Hound Labs logo, wrapping around the bottom to cover the larger center hole, and ending on the opposite side.
- Apply the second tamper-evident seal to the air cartridge using the same placement technique.

5. CERTIFY

- Place locked air and donor cartridges into lab sample bag and seal bag.
- Ask donor to sign on screen to certify collection. Collector signs on screen to certify collection.
- Place lab sample bag in overnight shipping envelope and attach pre-printed lab shipping airbill.
- Release samples for shipment to lab the same day as collection or the next business day.
- Select the OK button on the touchscreen to begin a new collection.
- Power off using Shut Down on menu. Perform cleaning and maintenance as defined in user manual.

Additional instructions and training resources are available at: https://houndlabs.com/collector-portal.